

Product Datasheet

Indoor Unheated Emergency Safety Shower

EXP-18G/85G(D)
EXP-18GS/85G(D)

EN and ANSI compliant floor mounted unheated emergency safety shower with stainless steel eye/face wash unit. For use in indoor applications not subject to the possibility of freezing or overheating.

Fitted with foot pedal as standard. Delivers 76 litres per minute of potable water from the shower and 12 litres per minute to the eye/face wash.

Available with either galvanised mild steel powder coated (G) or stainless-steel (GS) pipework.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel (GS) or galvanised mild steel (G)
OPERATING VALVE	Stainless steel, full bore, stay open ball valve (GS) or nickel plated brass, two piece stay open valve (G)
SHOWER NOZZLE	Injection moulded nylon 6
EYE WASH	Stainless steel
EYE WASH DIFFUSERS	Chrome plated brass retaining ring, stainless steel filter mesh, plastic body
STANDARD FINISH	De-scaled (GS) or green powder coated (G)
SERVICES	
WATER INLET	1¼" female BSP
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Pull handle
EYE WASH	Push plate or foot pedal
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	267mm (10.5in) x 714mm (28.1in) x 2322mm (91.4in)
WEIGHT	16kg (35lb)

General Arrangement Drawing

Indoor Unheated Emergency Safety Shower

EXP-18G/85G(D)

EXP-18GS/85G(D)

