

STD-40K

Mobile Self-Contained Emergency Safety Shower

The 114 litre capacity unheated mobile self-contained emergency safety shower with eye/face wash unit.

Incorporating a polypropylene lined cylinder, a stainless steel frame and large pneumatic tyres, making it easy to manoeuvre by one person.

For long distances or uneven surfaces an optional 'A' frame with towing hitch can be fitted.

In addition, the wheel spacing can be altered allowing the unit to fit through standard door openings.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK AND FITTINGS (GS)	Stainless steel
OPERATING VALVES	316L stainless steel
SHOWER SPRAY OUTLET	Machine moulded nylon 6
STANDARD FINISH	White gloss painted tank
SERVICES	
WATER INLET	½" quick release
DESIGN OPERATING PRESSURE	1.2 BAR G - PRE SET (17 PSI)
MINIMUM FLOW RATES	Shower: 76 litres/minute minimum (20 US Gallons). Eye/face wash: 12 litres/minute minimum (3 US Gallons)
ENVIRONMENTAL OPERATING TEMPERATURE	
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)
OPERATIONAL	
SHOWER SPRAY OPERATION	Hand lever
EYEBATH/HAND HELD OPERATION	Pull lid forward
WEIGHTS and DIMENSIONS	
DIMENSIONS - STANDARD ORIENTATION (WxDxH)	Non-assembled: 740mm (29.1in) x 1110mm (43.7in) x 1450mm (57.1in)
	Assembled: 740mm (29.1in) x 1365mm (53.7in) x 2400mm (94.5in)
WEIGHT (NO OPTIONS)	80kg (176lb)
CAPACITY	114 litre (30 US Gallons)

STD-40K

Mobile Self-Contained Emergency Safety Shower

