

STD-45G

Emergency Eye/Face Wash - Plumbed in

Wall-mounted emergency eye/face wash with integral lid to protect the bowl and diffusers against dust and debris.

This ANSI compliant, plumbed in eye/face wash is designed to be quick and simple to operate with high flow rate aerated diffusers for improved washing.



Specifications

MATERIALS OF CONSTRUCTION	
EYE/FACE WASH BOWL/LID	Acrylic Capped ABS
SERVICES	
WATER INLET	½" Female BSP
DESIGN OPERATING PRESSURE	2.0 to 6 BAR G (29 to 87 PSI)
TEST PRESSURE	10.3 BAR G (149 PSI)
MINIMUM FLOW RATES	12 litres/minute minimum (3 US Gallons)
ENVIRONMENTAL OPERATING TEMPERATURE	
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)
OPERATIONAL	
EYE/FACE WASH OPERATION	Pull lid forward to operate
WEIGHTS and DIMENSIONS	
DIMENSIONS - STANDARD ORIENTATION (WxDxH)	320mm (12.6in) x 362mm (14.3in) x 227mm (8.9in)
WEIGHT (NO OPTIONS)	3kg (7lb)

STD-45G

Emergency Eye/Face Wash - Plumbed in

