



Justrite Safety Group

# 621 Diamond Flex Lok™ Solid

Diamond Flex Lok™ Solid modular PVC platform.



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 621 Diamond Flex Lok™ Solid

Sensational fatigue relief due to its unique “flex” design underneath. A permanent interlocking system ensures that the mat will not come apart.

- Custom-built according to your ideal floor mat in shape and size
- Anti-slip deck-plate surface design
- Bevelled ramps are available, eliminating trip hazards and allowing for easy access on to and off of the mat surface

## Recommended use

- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

## Colors:

- Black
- Black/Yellow

## Sizes:

- 107cm x 152cm
- 107cm x 183cm
- 76cm x 152cm
- per m2

## Accessories:

- 621-Tile Diamond Flex Lok™ Solid Tile
- 621-Ramp Diamond Flex Lok™ Solid Bevel
- 621-Corner Diamond Flex Lok™ Solid Corner



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Diamond Flex Lok™ Solid

## General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	621
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Diamond Flex Lok™ Solid
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States
Type	Dry Areas - Heavy Duty PVC Flooring
Update trigger	20210310-1301
Usage Intensity	Heavy duty

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

## Tests

Fire rating EU	En 13501-1 Cfl-S2
Foam Battery	40 lb/in <sup>2</sup>
Hardness	85 Shore A
Slip Rating	R10
Coefficient Friction Dry	0.69

## Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	PVC
Material Group	PVC
Process	Injection Moulding

## Diamond Flex Lok™ Solid Black/Yellow

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
621S4260BY	107cm x 152cm	16	25
621S3060BY	76cm x 152cm	10.8	25
621S4272BY	107cm x 183cm	20	25

## Diamond Flex Lok™ Solid Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
621S0000BL	per m2	9.7	25

### Accessories

621-Tile Diamond Flex Lok™ Solid Tile    621-Ramp Diamond Flex Lok™ Solid Bevel    621-Corner Diamond Flex Lok™ Solid Corner