

STD-85G/P(D)

Emergency Eye/Face Wash - Plumbed in


Open stainless steel bowl, pedestal-mounted emergency eye/face wash featuring twin spray nozzles protected by dust covers which lift off upon activation via the push plate.

The flow regulator valve guarantees an optimum water flow.

The eye wash diffusers are fitted with fine mesh strainers and individual flow controllers designed to give a gentle flow of aerated water at 12 litres per minute as per the ANSI standard.

This unit is intended for indoor use but can be located outdoors where there is no risk of overheating or freezing.


Packing Dimensions:



Height (H) x Width (W) x Depth (D): 180mm x 330mm x 1190mm

Specifications

MATERIALS OF CONSTRUCTION	
EYE/FACE WASH BOWL/LID	Stainless steel
PEDESTAL	Stainless steel
SERVICES	
WATER INLET	1/2" Male BSP
DESIGN OPERATING PRESSURE	2.0 to 6 BAR G (29 to 87 PSI)
MINIMUM FLOW RATES	12 litres/minute minimum (3 US Gallons)
ENVIRONMENTAL OPERATING TEMPERATURE	
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)
OPERATIONAL	
EYE/FACE WASH OPERATION	Push plate operated
WEIGHTS and DIMENSIONS	
DIMENSIONS - STANDARD ORIENTATION (WxDxH)	380mm (14.9in) x 340mm (13.4in) x 900mm (35.4in)
WEIGHT (NO OPTIONS)	4kg (9lb)



Product Datasheet - G.A. Drawings

STD-85G/P(D)

Emergency Eye/Face Wash - Plumbed in

