

EXP-AH-45GS/P

Emergency Eye/Face Wash - Plumbed in

Pedestal mounted freeze protected emergency eye/face wash unit ideal for cold climates.

The eye/face wash has high flow rate aerated diffusers for improved washing action and incorporates an integral lid connected to the water valve for automatic operation when the lid is pulled down.

Available with stainless steel pipework.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK AND FITTINGS	Stainless steel with 150lb medium wall tubulars and fittings
OPERATING VALVE	Chrome plated brass
INSULATION & OUTER CASING	Polyurethane foam insulation with a medium density polyethylene impact resistant outer casing
STANDARD FINISH	White with green/white safety stripes
SERVICES	
WATER INLET	1 1/4" Male BSP
DESIGN OPERATING PRESSURE	2.0 to 6 BAR G (29 to 87 PSI)
TEST PRESSURE	10.3 BAR G (149 PSI)
MINIMUM FLOW RATES	12 litres/minute minimum (3 US Gallons)
HEATING TYPE	Trace tape heated and pre-insulated
HEATING LOAD	36 Watts
ELECTRICAL EQUIPMENT	ATEX Zone 1 & 2 Gas Groups IIA and IIB, Temp Class T3
ELECTRIC SUPPLY	230V Single Phase, 50/60Hz
ENVIRONMENTAL OPERATING TEMPERATURE	
MINIMUM AMBIENT OPERATING TEMPERATURE	-20° C (-4° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)
OPERATIONAL	
EYE/FACE WASH OPERATION	Pull lid forward to operate
WEIGHTS and DIMENSIONS	
DIMENSIONS - STANDARD ORIENTATION (WxDxH)	320mm (12.6in) x 640mm (25.2in) x 1224mm (48.2in)
WEIGHT (NO OPTIONS)	14kg (31lbs)

EXP-AH-45GS/P

Emergency Eye/Face Wash - Plumbed in

